NBS Data Sheet



0800 389 1420



admin@woodblocx-landscaping.co.uk

USING THIS DOCUMENT

Simply copy and paste the relevant clauses and options into your project documentation. If you need any assistance please call or email us.

Last updated May 2023

Uniclass:

Pr_45_63_63_89 Treated timber plant containers

CAWS:

Q31/296 Timber plant containers Q32/281 Timber plant containers Q31/297 Timber plant containers

System Outline

Product Reference - WBX-001

Manufacturer - WoodBlocX Ltd (www.woodblocx.co.uk)

*Planters to be installed as per manufacturers contract drawings

System Parts

BlocX - Pressure treated Pine

BlocX 10: 750mm long x 75mm wide x 100 mm high BlocX 5: 375mm long x 75mm wide x 100 mm high BlocX 4: 300mm long x 75mm wide x 100 mm high BlocX 3: 225mm long x 75mm wide x 100 mm high BlocX 2: 150mm long x 75mm wide x 100 mm high Angle BlocX 7: 150mm long x 75mm wide x 100mm high Angle BlocX 15: 150mm long x 75mm wide x 100mm high BlocX A45-L: 353mm long x 75mm wide x 100mm high BlocX A45-S: 322mm long x 75mm wide x 100mm high

Capping

Traditional: 100mm wide x 50mm high (length varies) Modern: 75mm wide x 50mm high (length varies)

System fixings

Angle Corner Plates: 1mm thick galvanised steel

Dowels: Recycled plastic

Groud fixings (optional)

Ground Spikes: 400mm galvanised steel

Angle Floor Brackets: 2mm thick, 90 x 90mm galvanised steel

INSTALLATION

Setting on Earth

Refer to WoodBlocX Standard Detail - Soft ground

Setting on Concrete / Paving

Refer to WoodBlocX Standard Detail - Hard ground

Setting on Rooftop

Refer to WoodBlocX Standard Detail - Rooftop

*Planters must be suitably lined as demonstrated in Standard Details

























